


**ARCTIC™ 3x3% FREEZE PROTECTED ATC™  
FOAM CONCENTRATE**

# CONCENTRATES



## SOLBERG



### Description

ARCTIC™ 3x3 FP ATC™ foam concentrate from SOLBERG® is a synthetic, alcohol-resistant freeze-protected foam concentrate used to effectively extinguish Class B hydrocarbon and polar solvent fuel fires at 3% solution. ARCTIC 3x3 FP ATC foam concentrate provides rapid extinguishment and excellent burn back characteristics. ARCTIC 3x3 FP ATC foam concentrate can be used with fresh, sea and brackish water.

### Application

ARCTIC 3x3 FP ATC foam concentrate can be applied to either Class B hydrocarbon or polar solvent fuel fires. The foam concentrate can be used to prevent re-ignition of a liquid spill and control hazardous odors. Foam non-air aspirating, as well as air aspirating equipment, including standard fire sprinkler heads, can be used to obtain maximum results. ARCTIC 3x3 FP ATC foam concentrate is compatible with most powder (dry chemical) agents.

### Performance

#### Fire Performance

ARCTIC 3x3 FP ATC foam concentrate has been tested to and meets the fire performance test criteria of European Standard EN 1568 Parts 3 & 4 (latest edition) and International Maritime Organization (IMO) MSC.1/Circ. 1312 (latest edition).

#### Foam Proportioning

ARCTIC 3x3 FP ATC foam concentrate can be proportioned at the proper foam solution percentage using most common proportioning devices such as:

- Eductors
- Inline balance pressure proportioners
- Ratio controllers
- Self-inducting nozzles

#### Storage

The temperature range for ARCTIC 3x3 FP ATC foam concentrate is 14° F to 120° F (-10° C to 49° C).

### Typical Physical Properties at 77° F (25° C)

Appearance:	White non-Newtonian liquid
Freezing Point:	14° F (-10° C) <i>(No quality loss after thawing)</i>
Maximum storage temp:	120° F (49° C)
pH:	7.0 - 8.5
Refractive index:	1.3750 - 1.3840
Specific gravity:	1.030 - 1.045
Viscosity:	4000 - 4600 cP*
Sediments:	None

\*Brookfield Viscometer Spindle #4, Speed 30 rpm

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 20 years.

### Compatibility

ARCTIC 3x3 FP ATC foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing of foam concentrates, consult Solberg Technical Services.

*Solberg is a global company that is a one-stop resource for firefighting foam concentrates and custom-designed foam suppression systems hardware, offering both traditional and innovative firefighting foam technology. [www.solbergfoam.com](http://www.solbergfoam.com)*

**Materials of****Construction Compatibility**

ARCTIC 3x3 FP ATC foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about material compatibility, consult Solberg Technical Services.

**Inspection**

ARCTIC 3x3 FP ATC foam concentrate or pre-mix solutions should be inspected annually per National Fire Protection Association (NFPA)

Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

**Environmental Information**

ARCTIC 3x3 FP ATC foam concentrate complies with the United States Environmental Protection Agency (USEPA) Stewardship Program—2015 Requirements.

**Certifications**

SOLBERG® manufactured products are thoroughly inspected and undergo rigorous quality control

tests. These evaluations analyze the foam's physical parameters and the finished product's fire performance. A Certificate of Analysis (CoA) is issued with every batch.

ARCTIC 3x3 FP ATC foam concentrate is Approved to European Standard EN 1568 Parts 3 & 4, and International Maritime Organization (IMO) MSC.1/Circ. 1312 Approved.

**Ordering Information**

ARCTIC 3x3 FP ATC foam concentrate is available in pails, drums, totes and bulk quantities.

PART NO.	DESCRIPTION	APPROXIMATE SHIPPING WEIGHT	APPROXIMATE CUBE
20088	ARCTIC 3x3 FP ATC, 5 gallon (20 litre) pail	45 lb (21 kg)	1.25 ft <sup>3</sup> (0.04 m <sup>3</sup> )
20089	ARCTIC 3x3 FP ATC, 55 gallon (200 litre) drum	495 lb (224 kg)	11.83 ft <sup>3</sup> (0.33 m <sup>3</sup> )
20090	ARCTIC 3x3 FP ATC, 265 gallon (1000 litre) tote	2465 lb (1118 kg)	50.05 ft <sup>3</sup> (1.42 m <sup>3</sup> )
20091	ARCTIC 3x3 FP ATC, bulk	Call Customer Services	

**SOLBERGFOAM.COM**

FORM NUMBER F-2012009-3

COPYRIGHT © 2014. ALL RIGHTS RESERVED.  
SOLBERG® AND ARCTIC™ ARE TRADEMARKS OF THE SOLBERG COMPANY OR ITS AFFILIATES.

**AMERICAS**

THE SOLBERG COMPANY  
1520 Brookfield Avenue  
Green Bay, WI 54313  
USA  
Tel: +1 920 593 9445

**EMEA**

SOLBERG SCANDINAVIAN AS  
Radøyvegen 721 - Olsvollstranda  
N-5938 Sæbøvågen  
Norway  
Tel: +47 56 34 97 00

**ASIA-PACIFIC**

SOLBERG ASIA PACIFIC PTY LTD  
3 Charles Street  
St. Marys NSW 2760  
Australia  
Tel: +61 2 9673 5300